




Eco-Priora[®]

1-800-UNILOCK | UNILOCK.COM


UNILOCK
PAVERS & WALLS



LAYING PATTERNS



Eco-Priora 5x10
RB_A



Eco-Priora 5x10
HB_E

APPLICATIONS



APPEARANCE

Edge Detail - Micro
Surface Texture - Smooth
Joint Spacing - 7mm
Void - 4.6-7.08%

TECHNOLOGIES

PERMEABLE
Can be installed to allow water to flow through

TECHNICAL INFORMATION

Conforms to ASTM C 936 Eligible for LEED v4.1 credits



BEECHWOOD

Single Units



RECTANGLE
120 x 240 x 80mm
4 ¾ x 9 ½ x 3 ⅛
245 units/Bundle
.31 Sq.Ft./Stone

		SMOOTH CLASSIC
Bundle Type		SINGLE
Plant Produced		MICHIGAN
Thickness (mm)		80MM

SQFT PER	Bundle	75.95
	Layer	10.85
	Section	-
	Stone	0.31

PER BUNDLE	Layers	7.00
	Sections	-

SOLDIER LNFT PER	SqFt	1.27
	Section	-
	Layer	13.78
	Bundle	96.46

SAILOR LNFT PER	SqFt	2.54
	Section	-
	Layer	27.56
	Bundle	192.91

UNITS PER	SqFt	3.23
	Section	-
	Bundle	245.00

LBS PER	Layer	397
	Section	-
	Bundle	2,778

COLORS	Reflectance	
Beechwood	SR n/a SRI n/a	✓

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on an optional, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.