



Pisa™

1-800-UNILOCK | UNILOCK.COM

UNILOCK
PAVERS & WALLS



APPLICATIONS



CROSS SECTIONS

Cross Sections are available on Unilock's Contractor web site under Products: contractor.unilock.com

APPEARANCE

Edge Detail - n/a
 Surface Texture - Split
 Joint Spacing - n/a
 Void - n/a

TECHNOLOGIES

CLASSIC™
 Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C 1372
 Eligible for LEED v4.1 credits

| | CORNER SPLIT | STANDARD SPLIT | TAPERED SPLIT | 12" COPING SPLIT | XL WALL SPLIT |
|--------------------|--------------|----------------|---------------|------------------|---------------|
| Bundle Type | SINGLE | SINGLE | SINGLE | SINGLE | SINGLE |
| Plant Produced | OHIO | OHIO | OHIO | OHIO | OHIO |
| Thickness (mm) | 150MM | 150MM | 150MM | 150MM | 150MM |

| FCFT PER | Bundle | 15.00 | 20.00 | 20.00 | 21.00 | 21.33 |
|----------|--------|-------|-------|-------|-------|-------|
| | Layer | 5.00 | 6.67 | 6.67 | 3.00 | 5.33 |
| | Stone | 0.83 | 0.33 | 0.33 | 0.25 | 0.67 |

| PER BUNDLE | Layers | 15.00 | 20.00 | 20.00 | 7.00 | 4.00 |
|------------|----------|-------|-------|-------|------|------|
| | Sections | 5.00 | 6.67 | 6.67 | 2.00 | 4.00 |

| LNFT PER | Bundle | - | 40.00 | 40.00 | - | 42.67 |
|----------|--------|---|-------|-------|---|-------|
| | Unit | - | 0.67 | 0.67 | - | 1.33 |

| UNITS PER | SqFt | 1.20 | 3.00 | 3.00 | 4.00 | 1.50 |
|-----------|---------|-------|-------|-------|-------|-------|
| | Section | 6.00 | 30.00 | 30.00 | 42.00 | 8.00 |
| | Bundle | 18.00 | 60.00 | 60.00 | 84.00 | 32.00 |

| LBS PER | Layer | 314 | 857 | 768 | 388 | 617 |
|---------|---------|-----|-------|-------|-------|-------|
| | Section | 314 | 1,285 | 1,153 | 1,357 | 617 |
| | Bundle | 943 | 2,570 | 2,305 | 2,714 | 2,467 |

| COLORS | Reflectance | Stock | Stock | Stock | Stock | Stock |
|---------|----------------|-------|-------|-------|-------|-------|
| Granite | SR.n/a SRI n/a | ✓ | ✓ | ✓ | ✓ | ✓ |
| River | SR.n/a SRI n/a | ✓ | ✓ | ✓ | ✓ | ✓ |
| Sierra | SR.n/a SRI n/a | ✓ | ✓ | ✓ | ✓ | ✓ |



GRANITE



RIVER



SIERRA

| Single Units | CORNER | STANDARD | TAPERED | XL WALL | COPING |
|--------------|---|--|--|--|--|
| | | | | | |
| | 200 x 150 x 300mm 7 7/8 x 5 7/8 x 11 7/8" 18 units/Bundle .83 Fc.Ft./Stone | 200 x 75 x 300mm 7 7/8 x 5 7/8 x 11 7/8" 60 units/Bundle .33 Fc.Ft./Stone | 300 x 75 x 300mm 7 7/8 x 5 7/8 x 11 7/8" 60 units/Bundle .33 Fc.Ft./Stone | 400 x 150 x 300mm 15 3/4 x 5 7/8 x 11 7/8" 32 units/Bundle .67 Fc.Ft./Stone | 400 x 150 x 300mm 11 7/8 x 3 x 11 7/8" 84 units/Bundle .25 Fc.Ft./Stone |

Notes: **XL Wall units are single units and are sold in full bundles only.** When purchased by the full bundle, 12" Coping bundle has 14 units of closed-end coping (7 left and 7 right). Closed-end 12" coping not sold separately. Maximum height - 36" (under optimum conditions). Higher walls can be achieved using geogrid reinforcement. The set back on Pisa wall is 3/4" every course or 1 1/2" every 2 courses. Retaining wall engineering software is also available free of charge at www.unilock.com. Walls greater than 4' in height require professional engineering. Tapered Units allow for a minimum 5' Radius. All measurements are nominal. Contact Unilock for more information.