



Pisa™

1-800-UNILOCK | UNILOCK.COM

UNILOCK
PAVERS & WALLS



	CORNER DOUBLE SPLIT CLASSIC	XL TAPERED SPLIT CLASSIC	COPING CLASSIC
Bundle Type	DOUBLE	SINGLE	DOUBLE
Plant Produced	CHICAGO	CHICAGO	CHICAGO
Thickness (mm)	150MM	150MM	75MM

FCFT PER	Bundle	30.01	21.33	20.34
	Layer	10.00	5.33	2.91
	Stone	1.67	0.67	0.48

PER BUNDLE	Layers	3.00	4.00	7.00
	Sections	6.00	-	2.00

LNFT PER	Bundle	-	42.67	82.95
	Unit	-	1.33	1.97

UNITS PER	SqFt	0.60	1.50	2.06
	Section	3.00	-	21.00
	Bundle	18.00	32.00	42.00

LBS PER	Layer	547	629	411
	Section	274	-	1,437
	Bundle	1,641	2,514	2,875

COLORS		Stock	Stock	Stock
Granite	SR.n/a SRI n/a	✓	✓	✓
Nevada	SR.n/a SRI n/a	✓	✓	✓
Sierra	SR.n/a SRI n/a	✓	✓	✓

APPLICATIONS



CROSS SECTIONS

Cross Sections are available on Unilock's Contractor web site under Products: contractor.unilock.com

APPEARANCE

Edge Detail - n/a
 Surface Texture - Split & Standard (coping)
 Joint Spacing - n/a
 Void - n/a

TECHNOLOGIES

CLASSIC™
 Budget-friendly traditional product mix

TECHNICAL INFORMATION

Conforms to ASTM C 1372
 Eligible for LEED v4.1 credits



GRANITE



NEVADA



SIERRA

Single Units		CORNER 200 x 150 x 300mm 7 7/8 x 5 7/8 x 11 7/8" 18 units/Bundle 1.67 Fc.Ft./Stone * 32 Corner Units/Bundle		COPING 300 x 75 x 300mm 11 7/8 x 3 x 11 7/8" 42 units/Bundle .48 Fc.Ft./Stone		XL UNIT 400 x 150 x 300mm 15 3/4 x 5 7/8 x 11 7/8" 32 units/Bundle .67 Fc.Ft./Stone
--------------	---	---	---	--	--	--

Notes: * XL WALL UNITS ARE SINGLE UNITS AND ARE SOLD IN FULL BUNDLES ONLY and are produced and sold on a required, refundable skid. Corner Units are produced and sold on a required, refundable skid. 12" Coping bundle has 16 units of closed-end coping (8 left and 8 right). Closed-end 12" coping not sold separately. Maximum height - 36" (under optimum conditions). Higher walls can be achieved using geogrid reinforcement. The set back on Pisa wall is 3/4" every course or 1/2" every 2 courses. Retaining wall engineering software is also available free of charge at www.unilock.com. Walls greater than 4' in height require professional engineering. All measurements are nominal. Contact Unilock for more information.