



Treo[®] Smooth


1-800-UNILOCK | UNILOCK.COM

UNILOCK
PAVERS & WALLS




| | | SMOOTH FINISH |
|-------------------------|--------------------|------------------|
| Bundle Type | | RANDOM |
| Plant Produced | | UXBRIGE/NEW YORK |
| Thickness (mm) | | 60MM |
| SQFT PER | Bundle | 116.87 |
| | Layer | 11.69 |
| | Section | - |
| | Stone | 0.56 |
| PER BUNDLE | Layers | 10.00 |
| | Sections | - |
| SOLDIER LNFT PER | SqFt | - |
| | Section | - |
| | Layer | - |
| | Bundle | - |
| SAILOR LNFT PER | SqFt | 1.57 |
| | Section | - |
| | Layer | 18.35 |
| | Bundle | 183.46 |
| UNITS PER | SqFt | 1.80 |
| | Section | - |
| | Bundle | 210.00 |
| LBS PER | Layer | 321 |
| | Section | - |
| | Bundle | 3,208 |
| COLORS | Reflectance | Stock |
| Fossil | SR .22 SRI 21 | ✓ |
| Steel Mountain | SR .30 SRI 31 | ✓ |

LAYING PATTERNS



Treo Fixed Random_R



Treo Fixed Random_S

APPLICATIONS



APPEARANCE

Edge Detail - Rounded
 Surface Texture - Smooth
 Joint Spacing - 7mm
 Void - 5.5%

TECHNOLOGIES

PERMEABLE

Can be installed to allow water to flow through

ENDURACOLOR™

Refined surface and long-lasting color

TECHNICAL INFORMATION




Conforms to ASTM C 936
 Eligible for LEED v4.1 credits - see page 19.



FOSSIL



STEEL MOUNTAIN

| | | | | | | |
|----------------------|---|--|---|--|---|---|
| Random Bundle |  | LARGE RECTANGLE 225 x 337.5 x 60mm 8 7/8 x 13 3/8 x 2 3/8" 60 units/Bundle .82 Sq.Ft./Stone |  | SQUARE 225 x 225 x 60mm 8 7/8 x 8 7/8 x 2 3/8" 70 units/Bundle .55 Sq.Ft./Stone |  | SMALL RECTANGLE 112.5 x 225 x 60mm 4 1/2 x 8 7/8 x 2 3/8" 80 units/Bundle .27 Sq.Ft./Stone |
|----------------------|---|--|---|--|---|---|

Notes: **SOLD IN FULL BUNDLES ONLY** and is produced and sold on a required, refundable skid. **Important:** A urethane rubber paver mat must be used to prevent scuffing when compacting on textured surfaces. All measurements are nominal. Contact Unilock for more information.