

Page 1 of 8



EUROSTONE BOND - BEIGE FOR NATURAL STONE PAVING JOINTS

SDS Revision Date (dd/mm/yyyy): 26/02/2019

SAFETY DATA SHEET

SECTION 1 - IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product name: Eurostone Bond

Details of the supplier of the safety data sheet

Supplier: Alliance Designer Products Inc.

225 Blvd Bellerose West

Laval, Quebec Canada H7L 6A1

www.alliancegator.com Telephone: 450-624-1611

24 hour Emergency Phone : 450-624-1611

Available hours: 8h-17h Monday to Friday

Recommended use: Polymeric sand for natural stone and cobble stone paver joints

Restrictions on use: N.A.

SECTION 2 - HAZARDS IDENTIFICATION

HAZARD CLASSIFICATIONS
PRODUCT CLASSIFICATIONS

DANGER



Carcinogenicity - Category 1A. Specific target organ toxicity – repeated exposure-Category 1.

Hazard statement(s)May cause cancer. Causes damage to organs (lungs) through prolonged or repeated

exposure.

Precautionary statement(s)

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have

been read and understood. Do not breathe dust and aerosol. Do not eat, drink or smoke when using this product. Wear protective gloves, protective clothing, eye and face

protection. Wash thoroughly after handling.

Response: IF exposed or concerned: Get medical advice. Get medical advice if you feel unwell.

Storage: Store locked up.

Disposal: Dispose of contents/container in accordance with local, regional, national and/or

international regulations in force.

Other hazards: No other effects shown.

See toxicological information, section 11





Page 2 of 8



EUROSTONE BOND - BEIGE FOR NATURAL STONE PAVING JOINTS

SDS Revision Date (dd/mm/yyyy): 26/02/2019

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

CAS no.	Common name and synonyms	Concentration (W/W)
14808-60-7	Silica, crystalline (Quartz)	34-36%

SECTION 4 - FIRST AID MEASURES

If swallowed, irritation, any type of overexposure or symptoms of overexposure occur during use of the product or persists after use, immediately contact a POISON CENTER, an EMERGENCY ROOM or a PHYSICIAN; ensure that the product safety data sheet is available.

Eye contact: Check for and remove any contact lenses. Immediately flush eyes with plenty of water

for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical

attention immediately.

Skin contact: In case of contact, immediately flush skin with plenty of water for at least 15 minutes

while removing contaminated clothing and shoes. Wash clothing before reuse. Clean

shoes thoroughly before reuse. Get medical attention immediately.

Inhalation: Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory

arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.

Ingestion: Wash out mouth with water. Do not induce vomiting unless directed to do so by medical

personnel. Never give anything by mouth to an unconscious person. Get medical

attention immediately.

Symptoms: Cough, breathing pain, eye redness. Recurrent bronchitis and permanent respiratory

embarrassment.

Effects (acute or delayed):Dust from the product may cause mechanical irritation of the eyes and respiratory tract.

May cause lung inflammation.

May cause silicosis.

Immediate medical attention and

special treatment: No specific treatment.

Treat symptomatically. Contact poison treatment specialist immediately

if large quantities have been ingested or inhaled.

SECTION 5 - FIRE FIGHTING MEASURES

Suitable extinguishing media: Use dry chemical, CO2, water spray (fog) or foam.

Unsuitable extinguishing media: Jets of water can facilitate the spread of fire.



Tel.: 450 624-1611 Fax: 450 624-1622 Toll free: 1 866-212-1611 www.alliancegator.com - Email: info@alliancegator.com



Page 3 of 8



FOR NATURAL STONE PAVING JOINTS SDS Revision Date (dd/mm/yyyy): 26/02/2019

Specific hazards arising from the

EUROSTONE BOND - BEIGE

hazardous product:

No specific hazard.

Hazardous combustion products: Carbon monoxide and dioxide.

Special protective equipment and precautions for fire-fighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal precautions: No action shall be taken involving any personal risk or without suitable training. Evacuate

> surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal

protective equipment (see Section 8).

Protective equipment and emergency procedures:

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental

pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up:

Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosionproof equipment. Dispose of via a licensed waste disposal contractor.

SECTION 7 - HANDLING AND STORAGE

Precautions for safe handling: Put on appropriate personal protective equipment (see Section 8). Eating, drinking

> and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Avoid exposure - obtain special instructions before use. Avoid contact with eyes, skin and clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous.

Do not reuse container.

Store in accordance with local regulations. Store in a segregated and approved area. Conditions for safe storage:

Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled

containers. Use appropriate containment to avoid environmental contamination.



Page 4 of 8



EUROSTONE BOND - BEIGE FOR NATURAL STONE PAVING JOINTS

SDS Revision Date (dd/mm/yyyy): 26/02/2019

Incompatibility: Strong oxidizing agents.

DEIGE

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

No CAS	Common name and synonyms	IDHL mg/m3	TWA mg/m3	STEL mg/m3	CEIL mg/m3
14808-60-7	Silica, crystalline (Quartz)	50	0.1	Not available	Not available

IDHL: Immediately Dangerous to Life or Health Concentrations

TWA: Time Weighted Average STEL: Short -Term Exposure Limit

CEIL: Ceiling Limit

Appropriate engineering controls: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other

engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation

equipment.

Individual protection measures: Wash hands, forearms and face thoroughly after handling chemical products, before

eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers

are close to the workstation location.

Eyes: DO NOT WEAR CONTACT LENSES Wear anti-splash safety goggles.

Hands: Chemical-resistant, impervious gloves complying with an approved standard should be

worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check

during use that the gloves are still retaining their protective properties.

Respiratory: If workers are exposed to concentrations above the exposure limit, they must use

appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards

of the product and the safe working limits of the selected respirator.

Others: Wear protective clothing with long sleeves and appropriate safety shoes at all times.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Physical state: Solid
Colour: Beige
Odour: Odorless
Odour threshold: Not available





Page 5 of 8



BEIGE

EUROSTONE BOND - BEIGE FOR NATURAL STONE PAVING JOINTS

SDS Revision Date (dd/mm/yyyy): 26/02/2019

: Hg Not applicable. Melting/Freezing point: >1500°C (2732°F) Initial boiling point/boiling range: >500°C (932°F) Flash point: Not applicable Lower flammable/explosive limit: Not applicable Upper flammable/explosive limit: Not applicable Not applicable Auto-ignition temperature: Evaporation rate: Not applicable Vapour pressure: Not applicable Vapour density: Not applicable

Relative density: $1,401-2,000 \text{ kg/L à } 20 ^{\circ}\text{C (water = 1)}$

Solubility in water: Insoluble
Partition coefficient - n-octanol/water: Not applicable
Decomposition temperature: Not available
Kinematic viscosity: Not applicable

SECTION 10 - STABILITY AND REACTIVITY

Reactivity: Stable under recommended conditions of storage and handling.

Chemical stability: The product is chemically stable under normal conditions of use.

Possibility of hazardous reactions: No dangerous or polymerization reactions will not occur under normal conditions of

use.

Conditions to avoid: Keep away from incompatible products.

Incompatible materials: None known.

Hazardous decomposition

products: Carbon monoxide and dioxide.

SECTION 11 - TOXICOLOGICAL INFORMATION

No CAS	Common name and synonyms	(1) LD oral	(2) LD skin	(3) LD skin	(4) LC gases	(5) LC vapours	(6) LC dusts-mist
14808-60-7	Silica, crystalline (Quartz)	>2000	Not	>5000	Not	Not	>5.00
			available		applicable	applicable	

- (1) LD50 oral mg/kg
- (2) LD50 skin mg/kg
- (3) LD50 skin mg/kg
- (4) LC50 inhalation ppmV 4h gases
- (5) LC50 inhalation mg/l 4h vapours
- (6) LC50 inhalation mg/l 4h dusts-mist

Routes of exposure: This product is absorbed through the respiratory tract.

Symptoms: Cough, breathing pain, eye redness. Recurrent bronchitis and permanent respiratory

embarrassment.





Page 6 of 8



EUROSTONE BOND - BEIGE FOR NATURAL STONE PAVING JOINTS

SDS Revision Date (dd/mm/yyyy): 26/02/2019

BEIGE

Delayed and immediate effects:Dust from the product may cause mechanical irritation of the eyes and respiratory

tract. May cause lung inflammation. May cause silicosis.

No CAS	Common name and synonyms	IARC	ACGIH	Mutagenicity	Effect on reproduction
14808-60-7	Silica, crystalline (Quartz)	1	A2	No effects shown.	No effects shown.

Cancer classification under IARC (International Agency for Research on Cancer)

Group 1: carcinogenic to humans.

Group 2A: probably carcinogenic to humans.

Group 2B: possibly carcinogenic to humans.

Group 3: not classifiable as to its carcinogenicity to humans.

Group 4: probably not carcinogenic to humans.

Cancer classification under ACGIH (American Conference of Governmental Industrial Hygienists)

Group A1: confirmed human carcinogen.

Group A2: suspected human carcinogen.

Group A3: confirmed animal carcinogen with unknown relevance to humans.

Group A4: not classifiable as a human carcinogen.

Group A5: not suspected as a human carcinogen.

SECTION 12 - ECOLOGICAL INFORMATION

No CAS	Common name and synonyms	%	Persistent	Bio-accumulation	Aquatic ecotoxicity
14808-60-7	Silica, crystalline (Quartz)	34-36	Yes	No	No
No CAS	Common name and synonyms	%	Ecotoxicity for aquatic organisims-Short term	Ecotoxicity for aquatic organisims-Long term	Environnemental effects
14808-60-7	Silica, crystalline (Quartz)	34-36	No known adverse effect to aquatic life.	No known adverse effect to aquatic life.	No known adverse effect to the environment.



Page 7 of 8



BEIGE

EUROSTONE BOND - BEIGE FOR NATURAL STONE PAVING JOINTS

SDS Revision Date (dd/mm/yyyy): 26/02/2019

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal Method: Methods of disposal: The generation of waste should be avoided or minimized wherever

possible. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal

legislation and any regional local authority requirements.

SECTION 14 - TRANPORT INFORMATION

	TDG	DOT	IMDG	IATA
UN number				
Proper shipping name	Not regulated	Not regulated	Not regulated	Not regulated
Transport hazardclass(es)				
Packing group				

Other information

Marine pollutant: No

IMDG:Not applicableExemption for limited quantity:Not applicableSpecial precautions:Not applicableOthers exemptions:Not applicable

SECTION 15 - REGULATORY INFORMATION

All ingredients are listed on the EINECS or in compliance with the inventory.

The customer is responsible for determining the PPE (personal protection equipment) code for this material.

The classification of the product and the SDS were developped in accordance with HPR.

No CAS	Common name and synonyms	%	DSL	NDSL	NPRI
14808-60-7	Silica, crystalline (Quartz)	34-36	×		

No CAS	Common name and synonyms	%	TSCA	PROP-65	Right to Know
14808-60-7	Silica, crystalline (Quartz)	34-36	X	X	X





Page 8 of 8



BEIGE

EUROSTONE BOND - BEIGE FOR NATURAL STONE PAVING JOINTS

SDS Revision Date (dd/mm/yyyy): 26/02/2019

SECTION 16 - OTHER INFORMATION

Date: 07/01/2019

1

Version:

Notice to the reader:

The manufacturer hereby declares that the information disclosed herein have been based on governmental sites and/or raw material suppliers'. The manufacturer has no control over the nature and content of such information. The manufacturer fully reproduces all the information it holds on the constituent of the product, at the time it is manufactured. The manufacturer does not assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. By this data sheet, the manufacturer hereby discloses all the potential dangers it has knowledge of and which might be related to the using or manipulation of the product in order to allow the proper care to be brought and use with regard to the product. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist and notification is hereby given to the user. Notice is hereby given that injury can derive therefrom if the foregoing is not respected. The manufacturer assumes no responsibility for personal and/or material damage, lost or injury of whichever nature caused or which may occur following the wrongful, inappropriate, negligent or abusive use or handling of the product or from not having read the herein contained information.